AK Scientific, Inc.

Safety Data Sheet (United States) Isobutyl acrylate, stabilized with 10-20 ppm MEHQ

1.Identification	
Product name:	Isobutyl acrylate, stabilized with 10-20 ppm MEHQ
Catalog#:	7768AF
IUPAC name:	Isobutyl acrylate
Product use restrictions:	Only for research and development use by, or directly under the supervision of, a technically qualified individual.
Company:	AK Scientific, Inc.
1 2	30023 Ahern Ave.
	Union City, CA 94587
Telephone:	(510) 429-8835
Fax:	(510) 429-8836
Website:	www.aksci.com
Emergency contact number	: 1-800-633-8253 United States & Canada
	1-801-629-0667 International

2.Hazard Identification:

GHS Classification (United States)

Flammable liquids (Category 3) Acute toxicity, Inhalation (Category 4) Acute toxicity, Dermal (Category 4) Skin irritation (Category 2) Skin sensitization (Category 1) Specific target organ toxicity - single exposure (Category 3), Respiratory system Acute aquatic toxicity (Category 2) Chronic aquatic toxicity (Category 3)

Pictogram(s)



Signal word:

Warning

Hazard statement(s)

H226	Flammable liquid and vapor.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s):

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.

P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	FIF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
	Rinse skin with water/shower.
P304+P340+P312	2 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for
	breathing. Call a poison center or doctor if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370+P378	In case of fire: Use dry sand, dry chemical, CO2, water spray or alcohol-resistant
	foam for extinction.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403 +P235	-
P405	Store locked up.
P501	Dispose of contents/container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC) or not covered by GHS:

None

3.Composition/Information on Ingredients

Synonyms:	Not available.
CAS#:	106-63-8
Purity:	99% (GC)
EC:	Not available.

4. First Aid Measures

General Information: Immediately remove any clothing contaminated by the product. Move out of dangerous area. Consult a physician and show this safety data sheet.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Obtain medical aid.

Skin contact: Immediately flush skin with running water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Obtain medical aid immediately.

Eye contact: Immediately flush open eyes with running water for at least 15 minutes. Obtain medical aid immediately.

Ingestion: Do NOT induce vomiting without medical advice. Rinse mouth with water. Never administer anything by mouth to an unconscious person. Obtain medical aid immediately.

Most important symptoms and effects, both acute and delayed: No further information available. Please see sections 2 and 11.

Indication of any immediate medical attention and special treatment needed: No further information available.

5. Fire Fighting Measures

Suitable extinguishing media: Use water spray, dry chemical, carbon dioxide, or chemical foam. Specific hazards arising from the chemical: Carbon oxides.

Advice for firefighters: As in any fire, wear a NIOSH-approved or equivalent, pressure-demand, self-contained breathing apparatus and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Wear protective

equipment and keep unprotected personnel away. Ensure adequate ventilation. Remove all sources of ignition. Prevent further leak or spill if safe to do so. For personal protective equipment, please refer to section 8.

Environmental precautions: Do not let product enter drains, other waterways, or soil.

Methods and materials for containment and cleaning up: Prevent further leak or spill if safe to do so. Vacuum, sweep up, or absorb with inert material and place into a suitable disposal container. Consult local regulations for disposal. See section 13 for further disposal information.

7. Handling and Storage

Precautions for safe handling: Avoid contact with skin, eyes, and personal clothing. Wash hands thoroughly after handling. Avoid breathing fumes. Use only with adequate ventilation. Wear suitable protective clothing, gloves, and eye/face protection. Keep away from sources of ignition. Minimize dust generation and accumulation. Keep container tightly closed. Open and handle container with care. Do not eat, drink, or smoke while handling.

Conditions for safe storage, including any incompatibilities: Store in a tightly-closed container when not in use. Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from sources of ignition. ,Store long-term at room temperature.

8. Exposure Controls/Personal Protection

Exposure limits:

OSHA PEL:	Not available.
NIOSH REL:	Not available.
ACGIH TLV:	Not available.

Appropriate engineering controls: Avoid contact with skin, eyes, and clothing. Wash hands before breaks and immediately after handling the product. Facilities storing or utilizing this material should be equipped with an eyewash fountain. Use adequate general and local exhaust ventilation to keep airborne concentrations low.

Personal protection

Eyes:	Based on an evaluation of the eye or face hazards present, wear chemical splash-resistant safety glasses or goggles with side protection. A face shield may be appropriate in some workplaces. Use eyewear tested and approved under appropriate government standards such as OSHA 29 CFR 1910.133 or EU EN166.
Hands:	Wear gloves selected based on an evaluation of the possible hazards to hands and skin, the duration of use, the physical conditions of the workplace, and the chemical resistance and physical properties of the glove material.
Skin and body:	Protective clothing must be selected based on the hazards present in the workplace, the physical environment, the duration of exposure, and other factors. No fabric can provide protection against all potential hazards; therefore it is important to select the appropriate protective clothing for each specific hazard. At the minimum, wear a laboratory coat and close-toed footwear.
Respiratory:	Respirators are not a substitute for accepted engineering control measures such as enclosure or confinement of the operation, general and local ventilation, and substitution of less toxic materials. When respiratory personal protective equipment is appropriate based on an assessment of respiratory hazards in the workplace, use a NIOSH- or CEN-certified respirator.

9.	Phy	ysical	and	Chemica	al Prop	perties
	•	1 0				

Physical State: Molecular Formula: Molecular Weight: Odor: Colorless liquid C7H12O2 128.17 Ester-like

AK Scientific, Inc.

Safety Data Sheet (United States) Isobutyl acrylate, stabilized with 10-20 ppm MEHQ

pH:	Not available.
Boiling Point Range:	132°C
Freezing/Melting Point:	-60.99°C
Flash Point:	32°C
Evaporation Rate:	Not available.
Flammability(solid,gas):	Please see section 2.
Explosive limits:	Not available.
Vapor Pressure:	9.58 hPa
Vapor Density:	Not available.
Solubility:	1.8g/l (water soluble)
Relative Density:	0.89
Refractive Index:	Not available.
Volatility:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Partition Coefficient:	Not available.

10. Stability and Reactivity

Reactivity: Chemical stability: Possibility of hazardous reactions: Conditions to avoid: Incompatible materials: Hazardous decomposition products: Not available. Stable under recommended temperatures and pressures. Not available. Dust generation. Strong oxidizing agents. Carbon oxides.

11. Toxicological Information

RTECS# Acute toxicity: Routes of exposure: Symptoms related to the physical,chemical and toxicological characteristics: Not available. Not available. Inhalation,eye contact,skin contact,ingestion. Skin contact may result in inflammation characterized by itching, scaling, reddening, blistering, pain or dryness. Eye contact may result in redness, pain or severe eye damage. Inhalation may cause irritation of the lungs and respiratory system. Overexposure may result in serious illness or death.

Carcinogenicity

IARC:	Not classified.
NTP:	Not listed.
OSHA:	Not listed.
Acute toxic effects:	Inflammation of the eye is characterized by redness, watering, and itching. Skin
	inflammation is characterized by itching, scaling, reddening, or, occasionally,
	blistering.

12. Ecological Information

Ecotoxicity: Persistence and degradability: Bioaccumulative potential: Mobility in soil: Other adverse effects: Not available. Not available. Not available. Not available. Not available.

13. Disposal Considerations

Disposal of waste:

Chemical waste generators must determine whether a discarded chemical is classified as hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR 261.3. Additionally, waste generators must

consult state and local hazardous waste regulations to ensure complete and accurate classification. Observe all federal, state and local regulations when disposing of the substance.

Disposal of packaging: Do not reuse containers. Dispose of as unused product.

14. Transportation Information

DOT (United States)	
UN number:	UN2527
Proper shipping name:	Isobutyl acrylate, stabilize
Transport hazard class:	3;Flammable Liquid
Packing group:	III
ΙΑΤΑ	
UN Number:	UN2527
Proper shipping name:	Isobutyl acrylate, stabilize
Transport hazard class:	3;Flammable Liquid
Packing group:	III
15. Regulatory Information	

TSCA (United States)

This product is on the EPA Toxic Substance Control Act (TSCA) inventory. The product is supplied solely for use in research and development by or under the supervision of a technically qualified individual as defined in 40 CFR § 720 et seq. The health risks have not been fully determined. Any information that is or becomes available will be supplied on the SDS.

California Proposition 65:	Not Available	
NFPA Rating:	Health:	Not available.
-	Flammability:	Not available.
	Instability:	Not available.

16. Additional Information

Revision Date: 01/29/2020 Printed Date: 02/14/2020

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall AK Scientific be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if AK Scientific has been advised of the possibility of such damages.